SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, Nobutaka Taniguchi, a citizen of Japan residing at Kawasaki, Japan and Hiroyoshi Tomita, a citizen of Japan residing at Kawasaki, Japan have invented certain new and useful improvements in

DELAY TIME ADJUSTING CIRCUIT COMPRISING FREQUENCY DIVIDERS
HAVING DIFFERENT FREQUENCY DIVISION RATES

of which the following is a specification : -

TITLE OF THE INVENTION

DELAY TIME ADJUSTING CIRCUIT COMPRISING
FREQUENCY DIVIDERS HAVING DIFFERENT FREQUENCY
DIVISION RATES

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to
a delay time adjusting circuit and, more

10 particularly, to a delay time adjusting circuit and
a delay time adjusting method which circuit and
method adjust a delay time of a signal transmitted
in a semiconductor integrated circuit.

2. Description of the Related Art

15 Conventionally, a semiconductor integrated
circuit, such as a DDR(Double Data Rate)-SDRAM,
which is required to operate at high speed and has a
DLL (Delay Locked Loop) circuit mounted thereon,
comprises a delay time adjusting circuit to adjust a

20 phase of a clock signal.

FIG.1 is a circuit diagram of the
conventional delay time adjusting circuit. As shown
in FIG.1, the conventional delay time adjusting
circuit comprises an input buffer 1, an output

25 buffer 5, frequency dividers 2 and 4, a DLL array 3,
a dummy circuit 6, a phase comparator 8 and a delay
adjuster 10.

In the conventional delay time adjusting
circuit, a clock signal is input into the input

30 buffer 1, which outputs a signal Cin. The frequency
divider 2 and the DLL array 3 are connected to the
input buffer 1. The frequency divider 4 and the
output buffer 5 are connected to an output terminal
of the DLL array 3. The frequency divider 2 outputs

35 a target clock signal tclk. The DLL array 3 outputs
a signal Cout. The output buffer 5 outputs a clock
signal delayed by the DLL array 3. The frequency

division rates of the frequency dividers 2 and 4 are equal.

The dummy circuit 6 is connected to the frequency divider 4 and outputs a delay clock signal dclk. The phase comparator 8 is connected to the frequency divider 2 and an output terminal of the dummy circuit 6, and feeds back a result signal 'out' to the delay adjuster 10, according to the supplied target clock signal tclk and the fed-back delay clock signal dclk. An output terminal of the delay adjuster 10 is connected to the DLL array 3. The delay adjuster 10 supplies a control signal CS to the DLL array 3.

FIG.2 is a circuit diagram of the DLL array 3 shown in FIG.1. As shown in FIG.2, the DLL array 3 comprises a switching unit 31 including a plurality of parallel-connected switches SW1 to SWn, and inverters INV1 to INVn respectively arranged to correspond to the switches SW1 to SWn. Switching of the switches SW1 to SWn included in the switching unit 31 is controlled by the controlling signal CS supplied by the delay adjuster 10. The signal Cin is delayed by a time td in each of the inverters INV1 to INVn.

In the above-mentioned delay time adjusting circuit, supposing that a delay time at the input buffer 1 is d1 and a delay time at the output buffer 5 is d2, a delay time at the dummy circuit 6 is (d1 + d2). Also, supposing that a delay time of the DLL array 3 is d3, the clock signal input into the input buffer 1 and output from the output buffer 5 is delayed by a time (d1 + d2 + d3).

Also, supposing that delay times at the frequency dividers 2 and 4 are d4, the clock signal input into the input buffer 1 and then input into the phase comparator 8 as the target clock signal

tclk is delayed by a time (d1 + d4). In this case, the clock signal input into the input buffer 1 and consequently input into the phase comparator 8 as the delay clock signal dclk is delayed by a time (d1

5   + d3 + d4 + (d1 + d2)).

Accordingly, a difference in the delay times between the target clock signal tclk and the delay clock signal dclk is (d1 + d2 + d3). This difference equals the delay time (d1 + d2 + d3) of

10   the clock signal input into the input buffer 1 and output from the output buffer 5. Thereby, in order to match phases of the clock signal input into the input buffer 1 and the clock signal output from the output buffer 5, the delay adjuster 10 adjusts the

15   delay time d3 of the DLL array 3 so that the difference (d1 + d2 + d3) in the delay times between the target clock signal tclk and the delay clock signal dclk equals a time corresponding to a number n (1, 2 or other natural numbers) of clocks of the

20   clock signal.

Here, a description will be given, with reference to FIG.3 to FIG.7, of operations of the above-mentioned delay time adjusting circuit. In a case, shown in FIG.3, where a phase of a delay clock

25   signal dclk indicated by FIG.3-(b) is a time F1 behind a phase of the target clock signal tclk indicated by FIG.3-(a), at so-called rise times T1, T2 and T3 when the target clock signal tclk rises from a low level (L) to a high level (H), the delay

30   clock signal dclk is at a low level (L). In this case, the phase comparator 8 supplies the delay adjuster 10 with a result signal 'out' indicating a judgment (decrease) that the phase of the delay clock signal dclk is behind the phase of the target

35   clock signal tclk.

Thereby, the delay adjuster 10 supplies the DLL array 3 with a control signal CS according

to the result signal 'out' so as to shorten a delay
time in the DLL array 3 by the time F1. These
operations match the phase of the delay clock signal
dclk to the phase of the target clock signal tclk.

5   Likewise, the same or analogous operations apply to
each of cases shown in FIG.4 to FIG.6, where a phase
of a delay clock signal dclk is a time F2, F3 or F4
(each longer than the time F1) behind a phase of the
target clock signal tclk.

10   In a case, shown in FIG.7, where a phase
of a delay clock signal dclk indicated by FIG.7-(b)
is a still longer time behind a phase of a target
clock signal tclk indicated by FIG.7-(a), at the
times T2 and T3, the delay clock signal dclk is at a
15   high level (H). In this case, the phase comparator
8 supplies the delay adjuster 10 with a result
signal 'out' indicating a judgment (increase) that a
first clock of the delay clock signal dclk is ahead
of a second clock of the target clock signal tclk.

20   Thereby, the delay adjuster 10 supplies
the DLL array 3 with a control signal CS according
to the result signal 'out' so as to lengthen a delay
time in the DLL array 3 by a time F5. In such a
case shown in FIG.7, the phase of the delay clock
25   signal dclk is matched to the phase of the target
clock signal tclk, based on the second clock of the
target clock signal tclk.

          FIG.8 is a circuit diagram of the phase
comparator 8 shown in FIG.1. As shown in FIG.8, the
30   phase comparator 8 comprises NAND circuits 80 to 85.
The target clock signal tclk is supplied to the NAND
circuits 81 and 82. The delay clock signal dclk is
supplied to the NAND circuit 83. The result signal
'out' is output from an output terminal of the NAND
35   circuit 84.

          FIG.9 is a waveform diagram indicating an
operation of the above-mentioned phase comparator 8

in a case where a first clock of a delay clock
signal dclk is behind a first clock of a target
clock signal tclk. FIG.9-(a) indicates the target
clock signal tclk. FIG.9-(b) indicates the delay
5 clock signal dclk. FIG.9-(c) indicates fluctuations
of electric potential at an output node NA of the
NAND circuit 81. FIG.9-(d) indicates fluctuations
of electric potential at an output node NB of the
NAND circuit 82. FIG.9-(e) indicates fluctuations
10 of electric potential at an output node NC of the
NAND circuit 80. FIG.9-(f) indicates fluctuations
of electric potential at an output node ND of the
NAND circuit 83. FIG.9-(g) indicates the result
signal 'out'.

15   In the case shown in FIG.9, where the
first clock of the delay clock signal dclk is behind
the first clock of the target clock signal tclk,
before a rise time TA of the target clock signal
tclk, the NAND circuits 84 and 85 latch the result
20 signal 'out' at a high level or a low level. Then,
at the rise time TA when the target clock signal
tclk rises to a high level, the electric potential
at the output node NB falls to a low level, and
consequently, the result signal 'out' is fixed at
25 the low level. Thereby, the phase comparator 8
supplies the delay adjuster 10 with the result
signal 'out' at the low level. That is, the phase
comparator 8 supplies the delay adjuster 10 with the
result signal 'out' indicating a judgment (decrease)
30 that the first clock of the delay clock signal dclk
is behind the first clock of the target clock signal
tclk.

         FIG.10 is a waveform diagram indicating an
operation of the above-mentioned phase comparator 8
35 in a case where a first clock of a delay clock
signal dclk is ahead of a first clock of a target
clock signal tclk. FIG.10-(a) indicates the target

clock signal tclk. FIG.10-(b) indicates the delay
clock signal dclk. FIG.10-(c) indicates
fluctuations of electric potential at the output
node NA of the NAND circuit 81. FIG.10-(d)

5   indicates fluctuations of electric potential at the
output node NB of the NAND circuit 82. FIG.10-(e)
indicates fluctuations of electric potential at the
output node NC of the NAND circuit 80. FIG.10-(f)
indicates fluctuations of electric potential at the

10   output node ND of the NAND circuit 83. FIG.10-(g)
indicates the result signal 'out'.

        In the case shown in FIG.10, where the
first clock of the delay clock signal dclk is ahead
of the first clock of the target clock signal tclk,

15   before the rise time TA of the target clock signal
tclk, the NAND circuits 84 and 85 latch the result
signal 'out' at a high level or a low level. Then,
at the rise time TA when the target clock signal
tclk rises to a high level, the electric potential

20   at the output node NA falls to a low level, and
consequently, the result signal 'out' is fixed at
the high level. Thereby, the phase comparator 8
supplies the delay adjuster 10 with the result
signal 'out' at the high level. That is, the phase

25   comparator 8 supplies the delay adjuster 10 with the
result signal 'out' indicating a judgment (increase)
that the first clock of the delay clock signal dclk
is ahead of the first clock of the target clock
signal tclk.

30   It should be noted that the above-
mentioned delay time of the DLL array 3 comprises a
variable component delay time that can be adjusted
by switching the switches SW1 to SWn included in the
switching unit 31, and a fixed component delay time

35   that is intrinsic to circuit properties of the DLL
array 3.

        The conventional delay time adjusting

circuit operates as mentioned above. However, as a
semiconductor integrated circuit is increasingly
made to operate at high speed, and accordingly, a
high-frequency signal is supplied to the input
5   buffer 1, the above-mentioned fixed component delay
time occupies a larger portion of a required total
delay time in a locking-on where the phases of the
delay clock signal and the target clock signal are
matched within a tolerance range.
10   As a countermeasure to this situation,
conventionally, the frequency division rates of the
frequency dividers 2 and 4 are raised so as to
postpone in time a target used in matching the
phases.
15   However, since dividing a frequency of the
clock signal by n in the frequency divider 2 means
that the target is postponed by a time corresponding
to 2^n clocks, when n is increased so as to raise the
above-mentioned frequency division rates, an
20   enormous number of the delay stages have to be
provided in the DLL array 3 in consideration of a
low-frequency band of the clock signal. This
increases a scale of the delay time adjusting
circuit.
25

SUMMARY OF THE INVENTION
            It is a general object of the present
invention to provide an improved and useful delay
time adjusting method and a delay time adjusting
30   circuit in which method and circuit the above-
mentioned problems are eliminated.
            A more specific object of the present
invention is to provide a delay time adjusting
method which can adjust a delay time of a signal at
35   high speed and a delay time adjusting circuit which
is reduced in scale but can realize the above-
mentioned method.

In order to achieve the above-mentioned objects, there is provided according to one aspect of the present invention a delay time adjusting circuit which adjusts a delay time of an input signal so that a phase of the input signal and a phase of an output signal match each other, the circuit comprising:

first dividing means for dividing a frequency of the input signal by a first frequency division rate;

delaying means for delaying the input signal by a predetermined time;

second dividing means for dividing a frequency of the input signal delayed by the delaying means by a second frequency division rate;

comparing means for comparing a phase of a signal generated by the first dividing means and a phase of a signal generated by the second dividing means; and

adjusting means for adjusting the predetermined time according to a comparison result obtained by the comparing means.

According to the present invention, the first dividing means for dividing a frequency of the input signal can change the first frequency division rate so that a target in adjusting the delay time can be set at arbitrary intervals. Thus, decreasing the first frequency division rate can shorten a time required to adjust the delay time, and can reduce a circuit scale of the delaying means for delaying the input signal. Also, the second dividing means for dividing a frequency of the delayed input signal can change the second frequency division rate so as to arbitrarily determine how frequently the phases are compared. Thus, increasing the second frequency division rate so as to compare the phases less frequently can reduce an amount of electric power to

be consumed.

Additionally, in the present invention, the first frequency division rate may be reduced to 1 so as to make unnecessary a circuit element that realizes the first dividing means for dividing a frequency, reducing a circuit scale. Additionally, the comparing means for comparing phases may supply a signal indicating the comparison result to the adjusting means according to the signal generated by the second dividing means for dividing a frequency. According to the present invention, changing the second frequency division rate in the second dividing means for dividing a frequency can adjust how frequently the phases are compared.

In order to achieve the above-mentioned objects, there is provided according to another aspect of the present invention a delay time adjusting method which adjusts a delay time of an input signal so that a phase of the input signal and a phase of an output signal match each other, the method comprising:

a first step of comparing a phase of a signal generated by dividing, by a first frequency division rate, a frequency of the input signal, and a phase of a signal generated by dividing, by a second frequency division rate, a frequency of the input signal delayed by a predetermined time; and

a second step of adjusting the predetermined time according to a comparison result obtained by the first step of comparing so that the phase of the signal generated by dividing by the first frequency division rate and the phase of the signal generated by dividing by the second frequency division rate match each other.

According to the present invention, the first frequency division rate can be changed so that a target in adjusting the delay time can be set at

arbitrary intervals. Thus, decreasing the first frequency division rate can shorten a time required to adjust the delay time. Also, the second frequency division rate can be changed so as to

5 arbitrarily determine how frequently the phases are compared. Thus, increasing the second frequency division rate so as to compare the phases less frequently can reduce an amount of electric power to be consumed.

10 Additionally, in the present invention, the first frequency division rate may be reduced to 1 so as to use the input signal as a target in comparing the phases. This way, the first step of comparing phases can obtain the comparison result

15 more quickly, enhancing a circuit operation speed. Additionally, in the second step, the above-mentioned predetermined time may be adjusted at a frequency according to the signal generated by dividing a frequency of the delayed input signal by

20 the second frequency division rate. According to the present invention, changing the second frequency division rate can adjust how frequently the phases are compared.

Other objects, features and advantages of

25 the present invention will become more apparent from the following detailed description when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

30 FIG.1 is a circuit diagram of a conventional delay time adjusting circuit;

FIG.2 is a circuit diagram of a DLL (Delay Locked Loop) array shown in FIG.1;

FIG.3 is a first waveform diagram

35 indicating an operation of the conventional delay time adjusting circuit shown in FIG.1;

FIG.4 is a second waveform diagram

indicating an operation of the conventional delay
time adjusting circuit shown in FIG.1;

FIG.5 is a third waveform diagram
indicating an operation of the conventional delay
time adjusting circuit shown in FIG.1;

FIG.6 is a fourth waveform diagram
indicating an operation of the conventional delay
time adjusting circuit shown in FIG.1;

FIG.7 is a fifth waveform diagram
indicating an operation of the conventional delay
time adjusting circuit shown in FIG.1;

FIG.8 is a circuit diagram of a phase
comparator shown in FIG.1;

FIG.9 is a waveform diagram indicating an
operation of the phase comparator shown in FIG.8 in
a case where a first clock of a delay clock signal
is behind a first clock of a target clock signal;

FIG.10 is a waveform diagram indicating an
operation of the phase comparator shown in FIG.8 in
a case where a first clock of a delay clock signal
is ahead of a first clock of a target clock signal;

FIG.11 is a circuit diagram of a delay
time adjusting circuit according to an embodiment of
the present invention;

FIG.12 is a circuit diagram of a delay
time adjusting circuit according to another
embodiment of the present invention;

FIG.13 is a first waveform diagram
indicating an operation of the delay time adjusting
circuit shown in FIG.12;

FIG.14 is a second waveform diagram
indicating an operation of the delay time adjusting
circuit shown in FIG.12;

FIG.15 is a third waveform diagram
indicating an operation of the delay time adjusting
circuit shown in FIG.12;

FIG.16 is a fourth waveform diagram

indicating an operation of the delay time adjusting
circuit shown in FIG.12;

FIG.17 is a fifth waveform diagram
indicating an operation of the delay time adjusting
circuit shown in FIG.12;

FIG.18 is a circuit diagram of a phase
comparator shown in FIG.12;

FIG.19 is a waveform diagram indicating an
operation of the phase comparator shown in FIG.18 in
a case where a first clock of a delay clock signal
is behind a first clock of a target clock signal;
and

FIG.20 is a waveform diagram indicating an
operation of the phase comparator shown in FIG.18 in
a case where a first clock of a delay clock signal
is ahead of a first clock of a target clock signal.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A description will now be given, with
reference to the drawings, of embodiments according
to the present invention. Elements in the drawings
that are identical or equivalent are referenced by
the same characters.

FIG.11 is a circuit diagram of a delay
time adjusting circuit according to an embodiment of
the present invention. As shown in FIG.11, the
delay time adjusting circuit according to the
present embodiment comprises the input buffer 1, the
output buffer 5, a first frequency divider 11, a
second frequency divider 12, the DLL array 3, the
dummy circuit 6, a phase comparator 9 and the delay
adjuster 10.

As described in detail hereinafter, the
first frequency divider 11 may be considered to be
an element that determines a target used in
adjusting a phase of a signal. The second frequency
divider 12 may be considered to be an element that

determines how frequently the phase of a signal has
a chance to be adjusted. Therefore, when a
frequency division rate of the second frequency
divider 12 is increased so that the phase of a
5   signal has a less frequent chance to be adjusted,
only a smaller amount of electric current is
consumed.

In the above-mentioned delay time
adjusting circuit, a clock signal is input into the
10   input buffer 1. The first frequency divider 11 and
the DLL array 3 are connected to the input buffer 1.
The second frequency divider 12 and the output
buffer 5 are connected to the output terminal of the
DLL array 3. The first frequency divider 11 outputs
15   the target clock signal tclk. The above-mentioned
delay time adjusting circuit is characterized in
that frequency division rates are different between
the first frequency divider 11 and the second
frequency divider 12.

20   The dummy circuit 6 is connected to the
second frequency divider 12 and outputs the delay
clock signal dclk. The phase comparator 9 is
connected to the first frequency divider 11 and the
output terminal of the dummy circuit 6, and outputs
25   the result signal 'out'. The delay adjuster 10 is
connected to the phase comparator 9, and the output
terminal of the delay adjuster 10 is connected to
the DLL array 3. The delay adjuster 10 supplies the
control signal CS to the DLL array 3.

30   The frequency division rate of the first
frequency divider 11 may be set to 1. In this case,
the first frequency divider 11 supplies an input
signal to the phase comparator 9 as it is. Hence,
the delay time adjusting circuit has a structure
35   equivalent to a delay time adjusting circuit shown
in FIG.12 without the first frequency divider 11,
wherein an output signal from the input buffer 1 is

supplied directly to the phase comparator 9 as the
target clock signal tclk. The delay time adjusting
circuit shown in FIG.12 requires a smaller number of
delay stages (the inverters INV1 to INVn) to be
5   included in a DLL array 7 than that of a
conventional technology, as mentioned hereinafter.

Next, a description will be given, with
reference to FIG.13 to FIG.17, of operations of the
above-mentioned delay time adjusting circuit shown
10   in FIG.12. Here, a frequency division rate of the
second frequency divider 12 shown in FIG.12 is set
to four.

Accordingly, a delay clock signal dclk
indicated by FIG.13-(b) has one fourth the frequency
15   of that of a target clock signal tclk indicated by
FIG.13-(a). In a case where a first clock of the
delay clock signal dclk is a time F6 behind a first
clock of the target clock signal tclk, at the rise
times T1, T2 and T3 when the target clock signal
20   tclk rises from a low level (L) to a high level (H),
the delay clock signal dclk is at a low level (L).
In this case, the phase comparator 9 supplies the
delay adjuster 10 with a result signal 'out'
indicating a judgment (decrease) that a phase of the
25   delay clock signal dclk is behind a phase of the
target clock signal tclk.

Thereby, the delay adjuster 10 supplies
the DLL array 7 with a control signal CS according
to the result signal 'out' so as to shorten a delay
30   time in the DLL array 7 by the time F6. These
operations match the phase of the delay clock signal
dclk to the phase of the target clock signal tclk.

In a case, shown in FIG.14, where a first
clock of a delay clock signal dclk indicated by
35   FIG.14-(b) is a longer time behind a first clock of
a target clock signal tclk indicated by FIG.14-(a),
at a time T4, the delay clock signal dclk is at a

high level (H). In this case, the phase comparator
9 supplies the delay adjuster 10 with a result
signal 'out' indicating a judgment (increase) that
the first clock of the delay clock signal dclk is
5   ahead of a second clock of the target clock signal
tclk. Thereby, the delay adjuster 10 supplies the
DLL array 7 with a control signal CS according to
the result signal 'out' so as to lengthen a delay
time in the DLL array 7 by a time F7. In such a
10   case shown in FIG.14, the phase of the delay clock
signal dclk is matched to the phase of the target
clock signal tclk, based on the second clock of the
target clock signal tclk.

     In a case, shown in FIG.15, where a first
15   clock of a delay clock signal dclk indicated by
FIG.15-(b) is an even longer time behind a first
clock of a target clock signal tclk indicated by
FIG.15-(a), at the time T4 when the target clock
signal tclk rises from a low level (L) to a high
20   level (H), the delay clock signal dclk is at a low
level (L). Accordingly, in this case, the phase
comparator 9 supplies the delay adjuster 10 with a
result signal 'out' indicating a judgment (decrease)
that the first clock of the delay clock signal dclk
25   is behind a second clock of the target clock signal
tclk.

     Thereby, the delay adjuster 10 supplies
the DLL array 7 with a control signal CS according
to the result signal 'out' so as to shorten a delay
30   time in the DLL array 7 by a time F8. These
operations match the phase of the delay clock signal
dclk to the phase of the target clock signal tclk.

     In a case, shown in FIG.16, where a phase
of a delay clock signal dclk indicated by FIG.16-(b)
35   is a still longer time behind a phase of a target
clock signal tclk indicated by FIG.16-(a), at a time
T5, the delay clock signal dclk is at a high level

(H). In this case, the phase comparator 9 supplies the delay adjuster 10 with a result signal 'out' indicating a judgment (increase) that a first clock of the delay clock signal dclk is ahead of a third

5 clock of the target clock signal tclk.

Thereby, the delay adjuster 10 supplies the DLL array 7 with a control signal CS according to the result signal 'out' so as to lengthen a delay time in the DLL array 7 by a time F9. In such a

10 case shown in FIG.16, the phase of the delay clock signal dclk is matched to the phase of the target clock signal tclk, based on the third clock of the target clock signal tclk.

In a case, shown in FIG.17, where a phase

15 of a delay clock signal dclk indicated by FIG.17-(b) is a yet longer time behind a phase of a target clock signal tclk indicated by FIG.17-(a), at the time T5 when the target clock signal tclk rises from a low level (L) to a high level (H), the delay clock

20 signal dclk is at a low level (L). Accordingly, in this case, the phase comparator 9 supplies the delay adjuster 10 with a result signal 'out' indicating a judgment (decrease) that a first clock of the delay clock signal dclk is behind a third clock of the

25 target clock signal tclk.

Thereby, the delay adjuster 10 supplies the DLL array 7 with a control signal CS according to the result signal 'out' so as to shorten a delay time in the DLL array 7 by a time F10. These

30 operations match the phase of the delay clock signal dclk to the phase of the target clock signal tclk.

FIG.18 is a circuit diagram of the phase comparator 9 shown in FIG.12. As shown in FIG.18, the phase comparator 9 comprises NAND circuits 90 to

35 95. The delay clock signal dclk is supplied to the NAND circuits 91 and 92. The target clock signal tclk is supplied to the NAND circuit 93. The result

signal 'out' is output from an output terminal of
the NAND circuit 95. As described in detail
hereinafter, the phase comparator 9 outputs the
result signal 'out' indicating a judgment made
5   according to a rise time of the delay clock signal
dclk. Accordingly, when a frequency division rate
of the second frequency divider 12 is increased so
that a phase of a signal has a less frequent chance
to be adjusted, only a smaller amount of electric
10   current is consumed.
        FIG.19 is a waveform diagram indicating an
operation of the above-mentioned phase comparator 9
in a case where a first clock of a delay clock
signal dclk is behind a first clock of a target
15   clock signal tclk. FIG.19-(a) indicates the target
clock signal tclk. FIG.19-(b) indicates the delay
clock signal dclk. FIG.19-(c) indicates
fluctuations of electric potential at an output node
NA of the NAND circuit 91. FIG.19-(d) indicates
20   fluctuations of electric potential at an output node
NB of the NAND circuit 92. FIG.19-(e) indicates
fluctuations of electric potential at an output node
NC of the NAND circuit 90. FIG.19-(f) indicates
fluctuations of electric potential at an output node
25   ND of the NAND circuit 93. FIG.19-(g) indicates the
result signal 'out'.
        In the case shown in FIG.19, where the
first clock of the delay clock signal dclk is behind
the first clock of the target clock signal tclk,
30   before a rise time TB of the delay clock signal dclk,
the NAND circuits 94 and 95 latch the result signal
'out' at a high level or a low level. Then, when
the delay clock signal dclk rises to a high level at
the rise time TB, the electric potential at the
35   output node NA falls to a low level, and
consequently, the result signal 'out' is fixed at
the low level. Thereby, the phase comparator 9

supplies the delay adjuster 10 with the result
signal 'out' at the low level. That is, the phase
comparator 9 supplies the delay adjuster 10 with the
result signal 'out' indicating a judgment (decrease)
5   that the first clock of the delay clock signal dclk
is behind the first clock of the target clock signal
tclk.

FIG.20 is a waveform diagram indicating an
operation of the above-mentioned phase comparator 9
10   in a case where a first clock of a delay clock
signal dclk is ahead of a first clock of a target
clock signal tclk. FIG.20-(a) indicates the target
clock signal tclk. FIG.20-(b) indicates the delay
clock signal dclk. FIG.20-(c) indicates
15   fluctuations of electric potential at the output
node NA of the NAND circuit 91. FIG.20-(d)
indicates fluctuations of electric potential at the
output node NB of the NAND circuit 92. FIG.20-(e)
indicates fluctuations of electric potential at the
20   output node NC of the NAND circuit 90. FIG.20-(f)
indicates fluctuations of electric potential at the
output node ND of the NAND circuit 93. FIG.20-(g)
indicates the result signal 'out'.

In the case shown in FIG.20, where the
25   first clock of the delay clock signal dclk is ahead
of the first clock of the target clock signal tclk,
before the rise time TB of the delay clock signal
dclk, the NAND circuits 94 and 95 latch the result
signal 'out' at a high level or a low level. Then,
30   when the delay clock signal dclk rises to a high
level at the rise time TB, the electric potential at
the output node NB falls to a low level, and
consequently, the result signal 'out' is fixed at
the high level. Thereby, the phase comparator 9
35   supplies the delay adjuster 10 with the result
signal 'out' at the high level. That is, the phase
comparator 9 supplies the delay adjuster 10 with the

result signal 'out' indicating a judgment (increase)
that the first clock of the delay clock signal dclk
is ahead of the first clock of the target clock
signal tclk.

5   In the above-mentioned cases, a frequency
division rate of the target clock signal tclk to an
input clock signal supplied to the input buffer 1 is
1. Therefore, the target clock signal tclk has a
higher frequency than that in a conventional delay

10   time adjusting circuit. Accordingly, clocks that
the phase comparator 9 can use as a target in
comparing the phases of the clock signals appear
more frequently in a unit period of time. Thereby,
since the nearest clock, whether behind or ahead, of

15   the target clock signal tclk to the first clock of
the delay clock signal dclk is used as a target in
matching the phases of the clock signals as
mentioned above, a time by which to match the phases
of the clock signals can be made smaller than in a

20   conventional delay time adjusting circuit.
          Hence, the delay time adjusting circuit
according to the present embodiment can shorten a
length of a delay-time adjustment so as to quickly
perform the adjustment of the delay time.

25   Additionally, in a low-frequency band of the input
clock signal supplied to the input buffer 1, the DLL
array 7 having a smaller number of the delay stages
(the inverters INV1 to INVn) than that of a
conventional technology is sufficient to adjust the

30   delay time. This reduces a scale of the delay time
adjusting circuit.
          The present invention is not limited to
the specifically disclosed embodiments, and
variations and modifications may be made without

35   departing from the scope of the present invention.
          The present application is based on
Japanese priority application No.2000-046226 filed

on February 23, 2000, the entire contents of which
are hereby incorporated by reference.